


# OMNIDRIVE

## 3.3" Diameter Totally Enclosed Construction

Kitchen/Bathroom Fans, Humidifiers, Unit Heaters, Fireplace Blowers



SS440



SS212S - SS212B - SS215



SS210 - SS217 - SS511

- Continuous duty
- Class 'B' insulation
- UL Listed & CSA Approved
- (●) Indicates motors are ball bearing
- Thermally protected
- 60 Hz
- Shaded pole & Sleeve bearing motors
- (~) Indicates motors are double shafted

Stock #	HP	Volts	Amps.	RPM	"A"	Shaft	Rotation	Comments	Replaces
SS440 ~	1/20	120	1.60	1550	3.10"	3.80" x 5/16" x 3.80"	CWLE	Double Shafted w/ Cord & Plug - Hex Hubs	Nutone
SS212S	1/30	240	0.55	1550	2.80"	5/16" x 3.50"	CWSE	Triangle Bracket	Chromalox
SS212B ●	1/35	240	0.55	1550	2.80"	5/16" x 3.50"	CWSE	Triangle Bracket	Chromalox
SS217	1/40	240	0.50	1550	2.30"	1/4" x 1.50"	CCWSE	24" Leads	Chromalox / FPE
SS210	1/50	230	0.40	1550	2.30"	1/4" x 1.50"	CWSE	23" Leads	Chromalox / FPE
SS215	1/300	240	0.24	1200	2.20"	5/16" x 2.25"	CWSE	Triangle Bracket - 24" Leads	Chromalox
SS511	1/350	230	0.38	1350	2.00"	1/4" x 2.00"	CCWSE	Groove on Shaft - 11" Leads	Blanchard / FPE



**UNIVERSAL ELECTRIC MOTORS**

DIVISION OF 1279311 ONTARIO INC.

6200 Dixie Road, Unit 1, Mississauga, Ontario, L5T 2E1

Tel: (905) 670-3380 - Toll free: 1-877-670-3380 - Fax: (905) 670-7637

WWW.UEM.CA - INFO@UEM.CA

