

# OMNIDRIVE

General Purpose & Farm Duty Motors  
Single Phase - Rolled Steel TEFC



All Models

- Rolled Steel Construction
- Ball Bearings
- Continuous Duty
- Class 'B' Insulation
- High Efficiency Capacitor Start/Run Design
- UL Listed & CSA Approved
- Reversible
- 40°C Ambient
- Removable Rigid Base
- Manual Overload

Stock #	Frame	HP	Volts	Amps.	RPM	"C"	Hz.	S.F.
FD141C	56C	1/3	115 / 208-230	4.70 / 2.50	3470	12.00"	60	1.15
FD142C	56C	1/2	115 / 208-230	5.90 / 3.10	3450	12.00"	60	1.15
FD143C	56C	3/4	115 / 208-230	8.10 / 4.20	3450	12.00"	60	1.15
FD144C	56C	1	115 / 208-230	8.30 / 4.40	3600	12.00"	60	1.15
FD145C	56C	1.5	115 / 208-230	14.00 / 7.00	3600	12.00"	60	1.15
FD146C	56C	2	115 / 208-230	16.20 / 8.40	3600	13.80"	60	1.15
FD147C	56C	3	208-230	12.40	3600	14.60"	60	1.15
FD161C	56C	1/3	115 / 208-230	4.30 / 2.30	1800	12.20"	60	1.15
FD162C	56C	1/2	115 / 208-230	5.80 / 3.00	1800	12.00"	60	1.15
FD163C	56C	3/4	115 / 208-230	8.10 / 4.20	1800	12.00"	60	1.15
FD164C	56C	1	115 / 208-230	9.20 / 5.00	1750	12.00"	60	1.15
FD165C	56C	1.5	115 / 208-230	13.30 / 7.10	1750	12.60"	60	1.15
FD166C	56HC	2	115 / 208-230	16.50 / 9.00	1800	14.20"	60	1.15
FD176	145T	2	115 / 208-230	16.50 / 8.30	1800	14.20"	60	1.15
FD176C	145TC	2	115 / 208-230	16.50 / 8.30	1800	14.20"	60	1.15



**UNIVERSAL ELECTRIC MOTORS**

DIVISION OF 1279311 ONTARIO INC.

6200 Dixie Road, Unit 1, Mississauga, Ontario, L5T 2E1

Tel: (905) 670-3380 - Toll free: 1-877-670-3380 - Fax: (905) 670-7637

WWW.UEM.CA - INFO@UEM.CA

