

# OMNIDRIVE

## NEMA 42 Frame / 5" Diameter

### Open Construction

Unit Heaters, Furnace Blowers, Refrigeration



- Continuous Duty
- Mechanically reversible
- Class "B" insulation
- UL Listed & CSA Approved
- Shaded pole
- Thermally protected
- 60 Hz.
- Sleeve Bearings

Stock #	HP	Volts	Amps.	RPM	"A"	Shaft	Rotation	Comments	Replaces
SS2398	1/8	115	5.00	1050	3.88"	1/2" x 3.75"	CWSE	Cushion Rings - 3 Speed Hex Hubs, 4 Bolt Mounting Pattern 2-9/16" x 4-1/8"	General Replacement
SS2930	1/10	115 / 230	4.10 / 2.00	1050	3.88"	3/8" x 2.80"	CWSE	Cushion Rings - Base 3/8" to 1/2" Bushing - 4 Studs on 3.50" B.C.D.	General Replacement Robbins & Myers GE 21/29 Frame
SS2932	1/10	115 / 208-230	5.00 / 2.50	1550	3.88"	3/8" x 2.88"	CCWSE	Cushion Rings - Base 3/8" to 1/2" Bushing - 4 Studs on 3.50" B.C.D.	General Replacement Robbins & Myers GE 21/29 Frame
SS2940	1/10	115 / 230	4.10 / 2.00	1050	3.88"	3/8" x 2.80"	CCWSE	Cushion Rings - Base 3/8" to 1/2" Bushing - 4 Studs on 3.50" B.C.D.	General Replacement Robbins & Myers GE 21/29 Frame
SS2942	1/10	115 / 208-230	5.00 / 2.50	1550	3.88"	3/8" x 2.88"	CWSE	Cushion Rings - Base 3/8" to 1/2" Bushing - 4 Studs on 3.50" B.C.D.	General Replacement Robbins & Myers GE 21/29 Frame
SS2605	1/12	115	3.00	1050	3.00"	1/2" x 3.00"	CCWSE	8" Cord & Plug, 4 Bolt Mounting Pattern 2-9/16" x 4-1/8"	Reversomatic
G018 •	1/10	600	0.64	1550	7.60"	1/2" x 7.23"	CWSE	Extended Thru-Bolts BX Connector	Federal Pioneer
F062 •	1/20	600	0.42	1550	6.45"	1/2" x 2.58"	CWSE	Tapped Holes on Shaft End	HACFM
SS2497	1/10	115	3.40	1100	2.25"	1/2" x 1-5/8"	CWSE	Includes Mounting Hardware	A0510B2497, A0416B2059, A0510B2389
SS8318	1/8	115	2.60	1550	3.50"	1/2" x 2-3/4"	CCWSE	4 Bolts - Mounted Capacitor	A0510B2497, A0416B2059, A0510B2389



## UNIVERSAL ELECTRIC MOTORS

DIVISION OF 1279311 ONTARIO INC.

6200 Dixie Road, Unit 1, Mississauga, Ontario, L5T 2E1

Tel: (905) 670-3380 - Toll free: 1-877-670-3380 - Fax: (905) 670-7637

WWW.UEM.CA - INFO@UEM.CA

