



OMNIDRIVE

NEMA Premium T-Frame Three Phase Motors Rolled Steel ODP



All Models



- Rolled Steel Construction
- Ball Bearing
- Continuous Duty
- Class 'F' Insulation
- UL Listed & CSA Approved
- 40°C Ambient
- Rigid Base
- Dual Mounting Holes in Base

Stock #	Frame	HP	Volts	Amps.	RPM	"C"	S.F.	Efficiency
ORP674	143T	1	208-230 / 460	3.20 / 1.60	1800	11.60"	1.15	85.5%
ORP654	143T	1	575	1.40	1800	11.60"	1.15	85.5%
ORP675	145T	1.5	208-230 / 460	4.50 / 2.20	1800	11.60"	1.15	86.5%
ORP655	145T	1.5	575	1.80	1800	11.60"	1.15	86.5%
ORP676	145T	2	208-230 / 460	5.90 / 2.90	1800	11.60"	1.15	86.5%
ORP656	145T	2	575	2.30	1800	11.60"	1.15	86.5%
ORP677	182T	3	208-230 / 460	8.00 / 4.00	1800	13.80"	1.15	89.5%
ORP657	182T	3	575	3.30	1800	13.80"	1.15	89.5%
ORP678	184T	5	208-230 / 460	13.20 / 6.60	1800	13.80"	1.15	89.5%
ORP658	184T	5	575	5.40	1800	13.80"	1.15	89.5%
ORP679	213T	7.5	208-230 / 460	19.00 / 9.50	1800	16.90"	1.15	91.0%
ORP659	213T	7.5	575	7.80	1800	16.90"	1.15	91.0%
ORP67A	215T	10	208-230 / 460	25.00 / 12.50	1800	16.90"	1.15	91.7%
ORP65A	215T	10	575	10.50	1800	16.90"	1.15	91.7%
ORP65B	254T	15	575	14.90	1800	19.75"	1.15	93.0%
ORP65C	256T	20	575	19.70	1800	19.75"	1.15	93.0%



UNIVERSAL ELECTRIC MOTORS

DIVISION OF 1279311 ONTARIO INC.

6200 Dixie Road, Unit 1, Mississauga, Ontario, L5T 2E1

Tel: (905) 670-3380 - Toll free: 1-877-670-3380 - Fax: (905) 670-7637

WWW.UEM.CA - INFO@UEM.CA

